



## KEY FEATURES

- Staff room refrigeration
- -18°C to -25°C temperature range
- Annual service and Calibration Available
- Fitted lock and 2 keys
- 2 year warranty as a standard

Gross Capacity (litres)	40.2
Net Capacity (litres)	40
Unit External Width (mm)	479
Unit External Depth (mm)	447
Unit External Height (mm)	522
Product Weight (kg)	17
Packed Width (mm)	515
Packed Depth (mm)	465
Packed Height (mm)	535
Packed Weight (kg)	19
Temperature Range	+2°C to +8°C (set point tolerance + or – 2)
Colour	White
External Finish	Painted Steel
Internal Finish	Painted Plastic
Battery Back up	No
Door Finish	Painted Steel/Solid
Door Type	Solid
Door Style	Hinged, Right hand
Door Liner	Flat
Door Open Depth (mm)	890
Replacement Door Seal	No
Open Door Sensor	No
Lock	Yes, 2 Keys
Adjustable Feet (number & position)	2 – adjustable
Porthole	No
Porthole Location	N/A
Temperature Display on Panel	No
Temperature Alarm	No
Remote Alarm Contacts	No
Audible Alarms	No
Visual Alarms	No
Number of Shelves	1
Number of Shelf Positions	1
Shelf Material	Plastic Coated Wire
Interior Light	No
Light Type	n/a
Light Activation	n/a
Fan	No
Spark Free	No
Controller Type	Manual thermostat
Number of Probes	1
Probe Type	Air only
Ambient Temperature Range	10°C to 30°C
Refrigerant Type	R600a
CFC Free	Yes
HCFC Free	Yes
Ammonia Free	Yes
UK 3 Pin Plug	Yes
Other Plug Types Available	No
Voltage Supply	220-240V / 50Hz
Blowing Agent	Cyclopentane
Wall Brackets	Yes
Optional Drawer System	No
Optional Digital Lock	Yes
Other Door Option	n/a
Certification	CE + UKCA
Noise Level (dbA)	50
Input Power (W)	76
Cable Length (CM)	150
Energy Consumption (KW/year)	187
Energy Consumption (KW/24hr)	0.5